

Characteristics	M.U.	EMO08BM1B	EMO08CM1B	EMO08GM1B
Cooling capacity EN814 - A35A35	W	820	820	820
Cooling capacity EN814 - A35A50	W	680	680	680
Power supply	V ~ Hz	230 1~ 50-60	115 1~ 50-60	400/440 2~ 50-60
Width	mm	348	348	348
Height	mm	783	783	783
Depth	mm	215	215+42**	215+58**
Max. current	A	2,6	5,3	1,7
Inrush current	A	10,8	21,5	6,1
Fuse T	A	6	10	6
Absorbed electric power EN814 - A35A35	W	440	450	450
Absorbed electric power EN814 - A35A50	W	490	500	500
Duty cycle	-	100 %	100 %	100 %
Electrical connection	-	4 pole plug	4 pole plug	4 pole plug
Refrigerant R134a	Kg	0,21	0,21	0,21
Cooling circuit max. pressure	bar	25	25	25
External fan air flow	m³/h	570	570	570
Enclosure fan air flow	m³/h	330	330	330
Internal temperature range	°C	+20/+46	+20/+46	+20/+46
Temperature setting	-	Electromechanical thermostat factory set at 35 °C		
External temperature range	°C	-20/+55*	-20/+50	-20/+50
Protection level EN60529 - enclosure side	-	IP54	IP54	IP54
Protection level EN60529 - ambient side	-	IP34	IP34	IP34
Noise level	dB (A)	65	65	65
Weight	Kg	27	28	28
Conformity	-	CE	CE	CE
Colour	-	RAL 7035 orange peel effect		


* 50 °C at 60 Hz

** Depth increases due to the external mounting of the autotransformer

Accessories/Options	
Pack of 5 cloth air filters	AAEFP10
Pack of 1 metal air filter	AAEFM10
Stainless steel version	
Special paint on request	
48VDC evaporator fan	
Anti vandalism fixing devices	
High temperature alarm	
Pressure alarms (high and low)	



Dimensions



Performances

